

IoT-Line Precision Balance KERN 572



- Protective working cover included with delivery

Technical data

- Large backlit LCD display, Digit height 21 mm
- Dimensions weighing surface, stainless steel
 - A** ϕ 106 mm
 - B** ϕ 150 mm
 - C** WxD 160x200 mm, see larger picture
- Overall dimensions WxDxH 180x310x85 mm
- Net weight **A**, **B** approx. 2,4 kg **C** approx. 2,8 kg
- Permissible ambient temperature -10 °C/40 °C

Accessories

- Protective working cover, scope of delivery: 5 items, KERN 572-A02S05
- Internal rechargeable battery pack, operating time up to 48 h without backlight, charging time approx. 8 h, KERN YKR-01
- External data interface RS-232, interface cable included, KERN KUP-01
- External data interface USB, interface cable included, KERN KUP-03
- Interface adapter Ethernet, KERN KUP-04
- Interface adapter WiFi, KERN KUP-05
- Bluetooth interface adapter, KERN KUP-06
- Extension box for connecting up to three interfaces in parallel, KERN KUP-13
- **B**, **C** Hook for underfloor weighing, KERN 572-A03
- **A** Large glass draught shield with 3 sliding doors for easy access to the items being weighed. Weighing space WxDxH 150x140x130 mm, for models with weighing plate size **A**, KERN 572-A05

All-rounder, e.g. as precision balance in the laboratory or in harsh industrial applications, ideal for the diverse possibilities of Industry 4.0 applications

Features

- Thanks to the many typical laboratory functions, such as, for example, recipe function, percentage determination, combined with the high level of precision, the KERN 572 is a reliable partner for day-to-day work in the laboratory
- The robust version, typical industrial functions, such as piece-counting, vibrationfree weighing and the large weighing ranges also make these balances ideal for all industrial applications, where a high level of precision is required
- KERN Universal Port (KUP): permits the connection of an external KUP interface adapter, such as, for example, RS-232, USB, Bluetooth, WiFi or Ethernet, for the exchange of data and control commands, without any installation outlay
- KERN Communication Protocol (KCP): The KCP permits searching and remote control of the balance using external control devices or computers
- For further information on KUP and KCP see page 20/21
- Standardised, simplified concept of operation
- Freely programmable weighing unit, e.g. display direct in special units such as length of thread g/m, paper weight g/m², or similar
- The robust aluminium diecast housing maintains the stability, protects the weighing technology elements and is robust enough to cope with everyday use
- **A** Ring-shaped draught shield standard, only for models with weighing plate size **A**, weighing space ϕ xH 157x43 mm
- Level indicator to level the balance precisely
- Underfloor weighing: load support on the underside of the balance for models. Loop for underfloor weighing, standard for models with weighing plate size **A**

STANDARD														OPTION						FACTORY			
														A		B		C					

Model	Weighing capacity [Max]	Readability	Reproducibility	Linearity	Resolution	Weighing plate	Options
	g	[d]	g	g	Points		DAkkS Calibr. Certificate
KERN		g					DAkkS KERN
572-30	240	0,001	0,001	± 0,003	240.000	A	963-127
572-31	300	0,001	0,002	± 0,005	300.000	A	963-127
572-32	420	0,001	0,002	± 0,005	420.000	A	963-127
572-33	1600	0,01	0,01	± 0,03	160.000	B	963-127
572-35	2400	0,01	0,01	± 0,03	240.000	B	963-127
572-37	3000	0,01	0,02	± 0,05	300.000	B	963-127
572-39	4200	0,01	0,02	± 0,05	420.000	B	963-127
572-45	12000	0,05	0,05	± 0,15	240.000	C	963-128
572-55	20000	0,05	0,1	± 0,25	400.000	C	963-128
572-43	10000	0,1	0,1	± 0,3	100.000	C	963-128
572-49	16000	0,1	0,1	± 0,3	160.000	C	963-128
572-57	24000	0,1	0,1	± 0,3	240.000	C	963-128