

NOMIS

SEISMOGRAPHS



Mini SUPERGRAPH

**THE LATEST COMPACT SEISMOGRAPH FOR
CONVENIENCE WITH THE MOST UPDATED FEATURES FOR
ACCURACY**

Features

- Standard sample rates up to 4000 samples per second
- 14 days monitoring without battery charging
- Self trigger (wave form) and Advanced Bar graph modes standard
- All results displayed on one LCD screen with back light
- Advanced cellular and modem operations including automatic email of data
- Unique option to name and save set up information
- Help menu on LCD
- No wait time between events so you will not miss consecutive events
- Quick and easy set up procedures
- Standard event memory storage for 700 events
- Complies with ISEE seismograph standards
- 2 Year Warranty on Parts & Labor

Mini SUPERGRAPH

TECHNICAL SPECIFICATIONS

SEISMIC

Seismic Monitoring (with Standard Triaxial Geophone)

Range	0 – 10 in/s (0-254 mm/s) - Standard
Resolution	.005 in/s
Accuracy	+/- 3%
Transducer Density	< 150 lbs/ft ³
Frequency Response	2 – 400 Hz (1 Hz optional)

Accelerometers Optional

SOUND

Weighting Scales	Linear (flat)
Linear Range	92-148 dB
Linear Resolution	.0025 milli bars
Linear Accuracy	+/- 1 dB or +/- 10 % whichever is greater
Linear Frequency Response	2 –400 Hz

WAVEFORM RECORDED DATA

Record Modes	Waveform & Manual
Seismic Trigger Range	.0075-10 in/s (.19-254 mm/s) , no trigger, manual Lower Levels Optional
Sound Trigger Range	
Linear	92 - 148 dBL, no trigger (other levels optional)
Sample Rate	1024 – 4096 Standard, Higher rates optional
Record Time	1-80 seconds
Cycle Time	No wait time between events
Storage Capacity	700 one second events standard @ 1024 samples/s

BAR GRAPH DATA

Record Modes	Bar Graph (Histogram)
LCD Readings	Real Time update 1-60 seconds selectable
Bar Recording Interval	1, 10, 20, 30, 40, 50, 60 seconds
Summary Interval	5, 15, 30 minutes, 1, 2, 4, 8,12, 24 hours
Summary Data	Peak R,T,V + Sound & Frequencies for each Choice of vector sum and displacement

PHYSICAL SPECIFICATIONS

Dimensions	6 x 4.25 x 3 in. (152 x 108 x 76 mm)
Weight	4.1 lbs. (1.9 kgs)
Battery	6 Volt, gel type rechargeable, 14 days duration
Display – LCD	8 lines x 21 characters with backlight
PC Interface	RS-232 & additional 15 pin auxiliary connector
Auxiliary Inputs and Outputs	External trigger & remote alarm
Operating Temperature	0 to 120 ⁰ F (-8 to 50 ⁰ C)
Remote Communications	Full function RS-232 Port, compatible with telephone, GSM, Satellite, RF

Promat (HK) Ltd

901 New Trend Centre, 704 Prince Edward Road, San Po Kong, Kowloon, Hong Kong

寶時(香港)有限公司 香港九龍新蒲崗太子道東 704 號新時代商業中心 901 室

Tel.: (852) 2661 2392 Fax.: 2661 2086 e-mail: info@promat.hk Website: http://www.promat.hk



Your Solution To Testing Instrument